

**120V N-Ch Power MOSFET**
**Feature**



- ◊ High Speed Power Switching
- ◊ Enhanced Body diode dv/dt capability
- ◊ Enhanced Avalanche Ruggedness
- ◊ 100% UIS Tested, 100% Rg Tested
- ◊ Lead Free, Halogen Free

$V_{DS}$	120	V
$R_{DS(on),typ}$   $V_{GS}=10V$	7.8	$m\Omega$
$I_D$ (Silicon Limited)	73	A
$I_D$ (Package Limited)	60	A

**Application**

- ◊ Synchronous Rectification in SMPS
- ◊ Hard Switching and High Speed Circuit
- ◊ DC/DC in Telecoms and Industrial

Part Number	Package	Marking
HGN093N12S	DFN5*6	GN093N12S

**DFN5x6**

**Absolute Maximum Ratings at  $T_j=25^\circ C$  (unless otherwise specified)**

Parameter	Symbol	Conditions	Value	Unit
Continuous Drain Current (Silicon Limited)	$I_D$	$T_C=25^\circ C$	73	A
Continuous Drain Current (Package Limited)		$T_C=100^\circ C$	46	
Pulsed Drain Current		$T_C=25^\circ C$	60	
Drain to Source Voltage	$V_{DS}$	-	120	V
Gate to Source Voltage	$V_{GS}$	-	$\pm 20$	V
Pulsed Drain Current	$I_{DM}$	-	250	A
Avalanche Energy, Single Pulse	$E_{AS}$	$L=0.1mH, T_C=25^\circ C$	101	mJ
Power Dissipation	$P_D$	$T_C=25^\circ C$	96	W
Operating and Storage Temperature	$T_J, T_{stg}$	-	-55 to 150	°C

**Absolute Maximum Ratings**

Parameter	Symbol	Max	Unit
Thermal Resistance Junction-Ambient	$R_{0JA}$	50	°C/W
Thermal Resistance Junction-Case	$R_{0JC}$	1.3	°C/W

**Electrical Characteristics at  $T_j=25^\circ\text{C}$  (unless otherwise specified)**
**Static Characteristics**







Parameter	Symbol	Conditions	Value			Unit
			min	typ	max	
Drain to Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}}=0\text{V}, I_D=250\mu\text{A}$	120	-	-	V
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{GS}}=V_{\text{DS}}, I_D=250\mu\text{A}$	2.0	3	4.0	
Zero Gate Voltage Drain Current	$I_{\text{DSS}}$	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=120\text{V}, T_j=25^\circ\text{C}$	-	-	1	$\mu\text{A}$
		$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=120\text{V}, T_j=100^\circ\text{C}$	-	-	100	
Gate to Source Leakage Current	$I_{\text{GSS}}$	$V_{\text{GS}}=\pm 20\text{V}, V_{\text{DS}}=0\text{V}$	-	-	$\pm 100$	nA
Drain to Source on Resistance	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}}=10\text{V}, I_D=20\text{A}$	-	7.8	9.3	$\text{m}\Omega$
Transconductance	$g_{\text{fs}}$	$V_{\text{DS}}=5\text{V}, I_D=20\text{A}$	-	60	-	S
Gate Resistance	$R_G$	$V_{\text{GS}}=0\text{V}, V_{\text{DS}} \text{ Open}, f=1\text{MHz}$	-	1.00	-	$\Omega$






**Dynamic Characteristics**


Input Capacitance	$C_{\text{iss}}$	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=60\text{V}, f=1\text{MHz}$	-	2509	-	pF
Output Capacitance	$C_{\text{oss}}$		-	306	-	
Reverse Transfer Capacitance	$C_{\text{rss}}$		-	10	-	
Total Gate Charge	$Q_g(10\text{V})$	$V_{\text{DD}}=60\text{V}, I_D=20\text{A}, V_{\text{GS}}=10\text{V}$	-	31	-	nC
Gate to Source Charge	$Q_{\text{gs}}$		-	10	-	
Gate to Drain (Miller) Charge	$Q_{\text{gd}}$		-	5	-	
Turn on Delay Time	$t_{\text{d}(\text{on})}$		-	12	-	
Rise time	$t_r$	$V_{\text{DD}}=60\text{V}, I_D=20\text{A}, V_{\text{GS}}=10\text{V}, R_G=10\Omega,$	-	7	-	ns
Turn off Delay Time	$t_{\text{d}(\text{off})}$		-	20	-	
Fall Time	$t_f$		-	9	-	




**Reverse Diode Characteristics**

Diode Forward Voltage	$V_{\text{SD}}$	$V_{\text{GS}}=0\text{V}, I_F=20\text{A}$	-	0.9	1.2	V
Reverse Recovery Time	$t_{\text{rr}}$	$V_R=60\text{V}, I_F=20\text{A}, dI_F/dt=100\text{A}/\mu\text{s}$	-	56	-	ns
Reverse Recovery Charge	$Q_{\text{rr}}$		-	78	-	nC

**Fig 1. Typical Output Characteristics**

**Figure 2. On-Resistance vs. Gate-Source Voltage**

**Figure 3. On-Resistance vs. Drain Current and Gate Voltage**

**Figure 4. Normalized On-Resistance vs. Junction Temperature**

**Figure 5. Typical Transfer Characteristics**

**Figure 6. Typical Source-Drain Diode Forward Voltage**


**Figure 7. Typical Gate-Charge vs. Gate-to-Source Voltage**

**Figure 8. Typical Capacitance vs. Drain-to-Source Voltage**

**Figure 9. Maximum Safe Operating Area**

**Figure 10. Maximum Drain Current vs. Case Temperature**

**Figure 11. Normalized Maximum Transient Thermal Impedance, Junction-to-Ambient**




**Package Outline**
**DFN5x6\_P, 8 Leads**

**Top View**  
**[顶视图]**

**Bottom View**  
**[底视图]**

**Side View**  
**[侧视图]**

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A3	0.254 REF		0.010REF	
D	4.680	5.120	0.184	0.202
E	5.900	6.126	0.232	0.241
D1	3.610	4.110	0.142	0.162
E1	3.380	3.780	0.133	0.149
D2	4.800	5.000	0.189	0.197
E2	5.674	5.826	0.223	0.229
k	1.100	1.390	0.043	0.055
b	0.330	0.510	0.013	0.020
e	1.270TYP		1.270TYP	
L	0.510	0.711	0.020	0.028
L1	0.424	0.576	0.017	0.023
H	0.410	0.726	0.016	0.029
$\theta$	0°	12°	0°	12°