

Feature

- ◊ High Speed Power Smooth Switching
- ◊ Enhanced Body diode dv/dt capability
- ◊ Enhanced Avalanche Ruggedness
- ◊ 100% UIS Tested, 100% Rg Tested
- ◊ Lead Free


Application

- ◊ Synchronous Rectification in SMPS
- ◊ Hard Switching and High Speed Circuit
- ◊ Power Tools
- ◊ UPS
- ◊ Motor Control

80V N-Ch Power MOSFET

V_{DS}	80	V
$R_{DS(on),typ}$	0.75	$m\Omega$
I_D (Silicon Limited)	585	A
I_D (Package Limited)	360	A

Part Number	Package	Marking
HGT009N08A	TOLL	GT009N08A

TOLL

Absolute Maximum Ratings at $T_i=25^\circ C$ (unless otherwise specified)

Parameter	Symbol	Conditions	Value	Unit
Continuous Drain Current (Silicon Limited)	I_D	$T_C=25^\circ C$	585	A
Continuous Drain Current (Package Limited)		$T_C=100^\circ C$	413	
		$T_C=25^\circ C$	360	
Drain to Source Voltage	V_{DS}	-	80	V
Gate to Source Voltage	V_{GS}	-	± 20	V
Pulsed Drain Current	I_{DM}	-	1800	A
Avalanche Energy, Single Pulse	E_{AS}	$L=0.4mH, T_C=25^\circ C$	720	mJ
Power Dissipation	P_D	$T_C=25^\circ C$	600	W
Operating and Storage Temperature	T_J, T_{stg}	-	-55 to 175	$^\circ C$

Absolute Maximum Ratings

Parameter	Symbol	Max	Unit
Thermal Resistance Junction-Case	R_{eJC}	0.25	$^\circ C/W$
Thermal Resistance Junction-Ambient	R_{eJA}	60	$^\circ C/W$

Electrical Characteristics at $T_j=25^\circ\text{C}$ (unless otherwise specified)
Static Characteristics

Parameter	Symbol	Conditions	Value			Unit
			min	typ	max	
Drain to Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=250\mu\text{A}$	80	-	-	V
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{GS}}=V_{\text{DS}}, I_{\text{D}}=250\mu\text{A}$	2	2.6	4	
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=80\text{V}, T_j=25^\circ\text{C}$	-	-	1	μA
		$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=80\text{V}, T_j=100^\circ\text{C}$	-	-	100	
Gate to Source Leakage Current	I_{GSS}	$V_{\text{GS}}=\pm 20\text{V}, V_{\text{DS}}=0\text{V}$	-	-	± 100	nA
Drain to Source on Resistance	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}}=10\text{V}, I_{\text{D}}=20\text{A}$	-	0.75	0.9	$\text{m}\Omega$
Transconductance	g_{fs}	$V_{\text{DS}}=5\text{V}, I_{\text{D}}=20\text{A}$	-	87	-	S
Gate Resistance	R_{G}	$V_{\text{GS}}=0\text{V}, V_{\text{DS}} \text{ Open}, f=1\text{MHz}$	-	0.64	-	Ω

Dynamic Characteristics

Input Capacitance	C_{iss}	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=40\text{V}, f=1\text{MHz}$	-	19090	-	pF
Output Capacitance	C_{oss}		-	2871	-	
Reverse Transfer Capacitance	C_{rss}		-	54	-	
Total Gate Charge	Q_g	$V_{\text{DD}}=40\text{V}, I_{\text{D}}=20\text{A}, V_{\text{GS}}=10\text{V}$	-	318	-	nC
Gate to Source Charge	Q_{gs}		-	60	-	
Gate to Drain (Miller) Charge	Q_{gd}		-	85	-	
Turn on Delay Time	$t_{\text{d}(\text{on})}$		-	36	-	
Rise time	t_r	$V_{\text{DD}}=40\text{V}, I_{\text{D}}=20\text{A}, V_{\text{GS}}=10\text{V}, R_{\text{G}}=10\Omega,$	-	32	-	ns
Turn off Delay Time	$t_{\text{d}(\text{off})}$		-	84	-	
Fall Time	t_f		-	26	-	

Reverse Diode Characteristics

Diode Forward Voltage	V_{SD}	$V_{\text{GS}}=0\text{V}, I_{\text{F}}=20\text{A}$	-	0.9	-	V
Reverse Recovery Time	t_{rr}	$V_{\text{R}}=40\text{V}, I_{\text{F}}=20\text{A}, \frac{dI_{\text{F}}}{dt}=100\text{A}/\mu\text{s}$	-	100	-	ns
Reverse Recovery Charge	Q_{rr}		-	221	-	nC



Fig 1. Typical Output Characteristics




Figure 2. On-Resistance vs. Gate-Source Voltage




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. Normalized On-Resistance vs. Junction Temperature




Figure 5. Typical Transfer Characteristics




Figure 6. Typical Source-Drain Diode Forward Voltage






Figure 7. Typical Gate-Charge vs. Gate-to-Source Voltage




Figure 8. Typical Capacitance vs. Drain-to-Source Voltage




Figure 9. Maximum Safe Operating Area




Figure 10. Maximum Drain Current vs. Case Temperature







Figure 11. Normalized Maximum Transient Thermal Impedance, Junction-to-Case





TOLL, 8 leads


SYMBOL	DIMENSIONS		
	MIN.	NOM.	MAX.
A	2.20	2.30	2.40
A1	1.70	1.80	1.90
b	0.70	0.80	0.90
b1	9.70	9.80	9.90
b3	1.90	2.00	2.10
c	0.40	0.50	0.60
D	10.28	10.38	10.48
D1	10.98	11.08	11.18
D2	3.20	3.30	3.40
D4	4.45	4.55	4.65
E	9.80	9.90	10.00
E1	8.00	8.10	8.20
E2	0.30	0.40	0.50
e	1.20 BSC		
H	11.58	11.68	11.78
H1	6.95 BSC		
H2	5.89 BSC		
i	0.10 REF.		
j	0.46 REF.		
K	2.80 REF.		
L	1.60	1.90	2.10
L1	0.60	0.70	0.80
L2	0.50	0.60	0.70
L3	0.60	0.70	0.80
N	8		
Q	6.80 REF.		
R	1.80	1.90	2.00
θ	10° REF.		