



60V P-Ch Power MOSFET
Feature

- ◇ High Speed Power Switching, Logic Level
- ◇ Enhanced Avalanche Ruggedness
- ◇ Lead Free, Halogen Free

V_{DS}	-60	V
$R_{DS(on),typ}$	$V_{GS}=10V$	125 mΩ
$R_{DS(on),typ}$	$V_{GS}=4.5V$	160 mΩ
I_D (Silicon Limited)	-2.2	A

Application

- ◇ Load Switches
- ◇ Hard Switching and High Speed Circuit
- ◇ BLDC Motor

SOT-23


Part Number	Package	Marking
HTJ1K5P06	SOT-23	28

Absolute Maximum Ratings at $T_j=25^\circ C$ (unless otherwise specified)

Parameter	Symbol	Conditions	Value	Unit
Continuous Drain Current (Silicon Limited)	I_D	$T_A=25^\circ C$	-2.2	A
		$T_A=70^\circ C$	-1.4	
Drain to Source Voltage	V_{DS}	-	-60	V
Gate to Source Voltage	V_{GS}	-	± 20	V
Pulsed Drain Current	I_{DM}	-	-8.8	A
Power Dissipation	P_D	$T_A=25^\circ C$	1.25	W
Operating and Storage Temperature	T_J, T_{stg}	-	-55 to 150	°C

Absolute Maximum Ratings

Parameter	Symbol	Max	Unit
Thermal Resistance Junction-Ambient	$R_{\theta JA}$	100	°C/W

Electrical Characteristics at $T_j=25^\circ\text{C}$ (unless otherwise specified)
Static Characteristics

Parameter	Symbol	Conditions	Value			Unit
			min	typ	max	
Drain to Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}}=0\text{V}, I_D=-250\mu\text{A}$	-60	-	-	V
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{GS}}=V_{\text{DS}}, I_D=-250\mu\text{A}$	-1.0	-1.70	-3.0	
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=-24\text{V}, T_j=25^\circ\text{C}$	-	-	-1	μA
		$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=-20\text{V}, T_j=125^\circ\text{C}$	-	-	-10	
Gate to Source Leakage Current	I_{GSS}	$V_{\text{GS}}=\pm20\text{V}, V_{\text{DS}}=0\text{V}$	-	-	±100	nA
Drain to Source on Resistance	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}}=-10\text{V}, I_D=-2\text{A}$	-	125	150	$\text{m}\Omega$
		$V_{\text{GS}}=-4.5\text{V}, I_D=-1.5\text{A}$	-	160	200	
Transconductance	g_{fs}	$V_{\text{DS}}=-5\text{V}, I_D=-2\text{A}$	-	3	-	S

Dynamic Characteristics

Input Capacitance	C_{iss}	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=-30\text{V}, f=1\text{MHz}$	-	1032	-	pF
Output Capacitance	C_{oss}		-	66	-	
Reverse Transfer Capacitance	C_{rss}		-	48	-	
Total Gate Charge	Q_g	$V_{\text{DD}}=-10\text{V}, I_D=-2\text{A}, V_{\text{GS}}=-10\text{V}$	-	12.3	-	nC
Gate to Source Charge	Q_{gs}		-	1.6	-	
Gate to Drain (Miller) Charge	Q_{gd}		-	2.4	-	
Turn on Delay Time	$t_{\text{d}(\text{on})}$		-	12	-	
Rise time	t_r	$V_{\text{DD}}=-10\text{V}, I_D=-1\text{A}, V_{\text{GS}}=-10\text{V}, R_G=6\Omega$	-	20	-	ns
Turn off Delay Time	$t_{\text{d}(\text{off})}$		-	20	-	
Fall Time	t_f		-	25	-	

Reverse Diode Characteristics

Diode Forward Voltage	V_{SD}	$V_{\text{GS}}=0\text{V}, I_F=-2\text{A}$	-		-1.2	V
-----------------------	-----------------	---	---	--	------	---







Fig 1. Typical Output Characteristics

Figure 2. On-Resistance vs. Gate-Source Voltage

Figure 3. On-Resistance vs. Drain Current and Gate Voltage

Figure 4. Normalized On-Resistance vs. Junction Temperature

Figure 5. Typical Transfer Characteristics

Figure 6. Typical Source-Drain Diode Forward Voltage


Figure 7. Typical Gate-Charge vs. Gate-to-Source Voltage




Figure 8. Typical Capacitance vs. Drain-to-Source Voltage




Figure 9. Maximum Safe Operating Area




Figure 10. Single Pulse Maximum Power Dissipation










Figure 11. Normalized Maximum Transient Thermal Impedance, Junction-to-Ambient





Package Outline
SOT-23, 3leads

Dimension in mm

Dimension	A	A1	A2	b	C	D	E	E1	e	e1	F	G	L1
Min.	0.7	0		0.35	0.1	2.8	2.6	1.5	0.9		0.8	0.3	0.55
Typ.						2.9	2.8	1.6	0.95	1.9			
Max.	1.12	0.1		0.5	0.2	3	3	1.7	1		1.2	0.6	0.65